

FIBER GASKET SETS

Durlon® 9000 – Chlorine Institute Approved



CHLORINE INSTITUTE APPROVED

Durlon® 9000 has successfully completed the Chlorine Institute Test Protocol and is listed in Pamphlet 95, Edition 3 as an approved gasket material for dry chlorine service (both liquid and gaseous).



AFGS

CHLORINE INSTITUTE EMERGENCY KIT-A
FIBER GASKET SET INCLUDES:

- (5) 2B Gasket, 15/16" Dia. x 1/16" Durlon® 9000
- (5) 2BB Gasket, 1" x 3" x 1/16" Rec. Durlon® 9000
- (5) A-5 Vent Valve Packing, Garlock
- (5) A-12 Washer, 15/16" O.D. x 9/16" I.D. x 1/16", Durlon® 9000
- (1) A-13 Plastic Box

AFGS



BFGS

CHLORINE INSTITUTE EMERGENCY KIT-B
FIBER GASKET SET INCLUDES:

- (3) 4D 1-1/4" OD x 11/16" ID x 1/16" Durlon® 9000
- (5) 4G Gasket, 15/16" Dia. x 1/16" Durlon® 9000
- (5) 4GG Gasket, 1" x 3" x 1/16" Rec. Durlon® 9000
- (5) B-4 Vent Valve Packing, Garlock
- (5) B-11 Washer, 15/16" O.D. x 9/16" I.D. x 1/16", Durlon® 9000
- (1) B-12 Plastic Box

BFGS

DURLON® 9000

Pure PTFE resins homogeneously blended with various inorganic fillers.

PROPERTY		VALUE
	Color	Blue
	Filler	Inorganic
	Temperature Range	-350°F to 520°F (-212° to 271°C)
	Pressure Max	1500 psig (103 bar)
	Density	2.2 g/cm³ (138 lbs./ft.³)
	Tensile Strength (ASTM F152)	2,000 psi (13.8 MPa)
	Compressibility (ASTM F36)	8 to 16%
	Recovery (ASTM F36)	40%



10 YEAR
RECOMMENDED
SHELF LIFE

Gaskets have a recommended
10 year shelf-life or after each use.

INDIAN SPRINGS
MANUFACTURING



315.635.6101

P.O. BOX 469
BALDWINVILLE, NY 13027-0469



sales@indiansprings.com



www.indiansprings.com